



MULTITECH



ROTEC
INTERNATIONAL

www.rotectbeds.com

MULTI-TECH



SPECIFICATIONS

- Load capacity: 227 kg (500 lbs)
- Bed weight: 95 kg (209 lbs)
- Minimum height: 30.5 cm (12 in.)
- Maximum height: 76.2 cm (30 in.)
- Maximum backrest angle: 70 degrees
- Maximum footrest angle: 40 degrees
- Available bedspring dimensions:
 - 88.9 cm (35 in.) x 190.5 cm (75 in.) or 203.2 cm (80 in.)
 - 99.1 cm (39 in.) x 190.5 cm (75 in.) or 203.2 cm (80 in.)
 - 121.9 cm (48 in.) x 190.5 cm (75 in.) or 203.2 cm (80 in.)
- Recommended mattress height: 12.7 cm (5 in.)

FEATURES

- Whisper-quiet direct-current linear motor
- IP54-approved electrical components protected from dust and water infiltration
- 2 receptacles for IV holder stems
- Battery ensuring temporary autonomous operation
- Casters equipped with individual brakes (2 with, 2 without)
- Possibility of moving the bed even when in its lowest height position
- Metal surfaces covered with electrostatic powder paint
- Selectable, manually adjustable foot angle (choice of two positions: flexion and standard)
- Ideal bed for home care patients or long-term care facilities
- Authentic Canadian product

OPTIONS

- Rotating half-length bed sides
- Tilting half-length bed sides
- Half-length metal bed sides
- Full-length metal bed sides
- Full-length Rotec bed sides
- Cast composite or wood headboard and footboard
- Trapeze bar (which follows the bed motions when adjusting in height)
- Nurse control or function limiter
- Variable-height pedal control system
- Composite bedspring overlay
- Transportation dolly

MULTI-TECH

*Photos and specifications may change without prior notice.

Vertical line on the left side of the page.